

Description

Fastener Length: 45/64", Thread Size: 3/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL10VF66
Minimum Qty (MOQ):	10
NSN:	5320-01-151-8800
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N HL10VF6-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Identification Code Color:	Blue
Fastener Length:	0.690 Inches Minimum And 0.710 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Unable To Decode:	Unable To Decode
Grip Length:	0.370 Inches Minimum And 0.380 Inches Maximum
Nominal Thread Size:	0.190 Inches
Shear Strength:	5380 Double Pounds Per Square Inch
Special Features:	U/w Collars HI70,HI79,HI82,HI94k,HI94v,HI97k,HI97v,HI379v And HI379sy
Heat Treatment:	As Fabricated Overall
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Surface Treatment Document And Classification:	Spec 306,type 1 Color Blue Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	73197-HI10 Manufacturers Standard

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL10VF6-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.