

Description

HL110V8-11 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL110V811
Minimum Qty (MOQ):	2
NSN:	5320-01-643-3620
ECCN:	EAR99



P/N HL110V8-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.0725 Inches Minimum And 1.0925 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.059 Inches Minimum And 0.069 Inches Maximum
Width Between Flats:	0.0947 Inches Minimum And 0.0967 Inches Maximum
Shank Diameter:	0.2641 Inches Minimum And 0.2651 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.387 Inches Minimum And 0.412 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
End Item Identification:	B1-bacft
Grip Length:	0.6825 Inches Minimum And 0.6925 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.2500 Inches
Shear Strength:	10490 Double Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Hi-lok Pin
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Or Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL110V8-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.