

## **P/N HL110VAZ6-10**

### **Description**

protruding shear head, oversized titanium

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: HL110VAZ610

Minimum Qty (MOQ): 10

NSN: 5320-01-451-7584

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# P/N HL110VAZ6-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.040 Inches Minimum And 1.060 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.080 Inches Maximum
Shank Diameter:	0.202 Inches Nominal
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Grip Length:	0.620 Inches Minimum And 0.630 Inches Maximum
Nominal Thread Size:	0.190 Inches
Material:	Titanium Alloy Uns R56400 Overall
Thread Series Designator:	Unjc

## **How to Order**

Order this pin-rivet from our inventory online by visiting <a href="https://military-fasteners.com/pins/pin\_rivets/HL110VAZ6-10">https://military-fasteners.com/pins/pin\_rivets/HL110VAZ6-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/pins/pin\_rivets/HL110VAZ6-10">https://military-fasteners.com/pins/pin\_rivets/HL110VAZ6-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/pins/pin\_rivets/HL110VAZ6-10">https://military-fasteners.com/pins/pin\_rivets/HL110VAZ6-10</a> and selecting the quantity you want then click "add to cart".