

Description

protruding shear head, oversized titanium

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL110VAZ610 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-451-7584 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

P/N HL110VAZ6-10 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 1.040 Inches Minimum And 1.060 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.045 Inches Minimum And 0.055 Inches Maximum |
| Width Between Flats: | 0.079 Inches Minimum And 0.080 Inches Maximum |
| Shank Diameter: | 0.202 Inches Nominal |
| Head Major Diameter: | 0.295 Inches Minimum And 0.315 Inches Maximum |
| Grip Length: | 0.620 Inches Minimum And 0.630 Inches Maximum |
| Nominal Thread Size: | 0.190 Inches |
| Material: | Titanium Alloy Uns R56400 Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL110VAZ6-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.