

## Description

protruding shear head, oversized titanium

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	HL110VAZ610
Minimum Qty (MOQ):	10
NSN:	5320-01-451-7584
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N HL110VAZ6-10 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	1.040 Inches Minimum And 1.060 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.045 Inches Minimum And 0.055 Inches Maximum
<b>Width Between Flats:</b>	0.079 Inches Minimum And 0.080 Inches Maximum
<b>Shank Diameter:</b>	0.202 Inches Nominal
<b>Head Major Diameter:</b>	0.295 Inches Minimum And 0.315 Inches Maximum
<b>Grip Length:</b>	0.620 Inches Minimum And 0.630 Inches Maximum
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL110VAZ6-10](https://military-fasteners.com/pins/pin_rivets/HL110VAZ6-10) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.