

Description

protruding shear head, oversized titanium

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL110VAZ610
Minimum Qty (MOQ):	10
NSN:	5320-01-451-7584
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N HL110VAZ6-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.040 Inches Minimum And 1.060 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.080 Inches Maximum
Shank Diameter:	0.202 Inches Nominal
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Grip Length:	0.620 Inches Minimum And 0.630 Inches Maximum
Nominal Thread Size:	0.190 Inches
Material:	Titanium Alloy Uns R56400 Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL110VAZ6-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.