

Description

protruding shear head, oversized titanium

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL110VAZ68
Minimum Qty (MOQ):	10
NSN:	5320-01-462-0392
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N HL110VAZ6-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.825 Inches Nominal
Head Style:	Err-090
Head Height:	0.050 Inches Nominal
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.2016 Inches Minimum And 0.2026 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.305 Inches Nominal
Lubrication:	Cetyl Alcohol
Grip Length:	0.500 Inches Nominal
Nominal Thread Size:	0.190 Inches
Special Features:	0.016 In Oversize Shank Dia; Color Coded Black
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Alloy Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL110VAZ6-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.