

Description

HL111VAZ6-11 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL111VAZ611 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-277-6265 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



* See page 2 for technical characteristics

P/N HL111VAZ6-11 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 1.003 Inches Minimum And 1.023 Inches Maximum |
| Head Style: | Flush Countersunk |
| Width Between Flats: | 0.0791 Inches Minimum And 0.0806 Inches Maximum |
| Shank Diameter: | 0.2021 Inches Minimum And 0.2026 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.2966 Inches Minimum And 0.3016 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Grip Length: | 0.693 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Special Features: | Color Code Black On Thread End |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | 294,cagec 73197 Mfr Ref Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL111VAZ6-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.