

**Description**

Flush shear head, oversized, titanium

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL111VAZ63
Minimum Qty (MOQ):	20
NSN:	5320-01-373-4922
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N HL111VAZ6-3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.503 Inches Minimum And 0.523 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Shank Diameter:</b>	0.201 Inches Minimum And 0.206 Inches Maximum
<b>Shank Style:</b>	Pin-rievet, Tapered, Threaded
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.301 Inches Maximum
<b>Tip Diameter:</b>	0.181 Inches Minimum And 0.184 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Grip Length:</b>	0.183 Inches Minimum And 0.193 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	2000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Shear Strength:</b>	6130 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4928 Assn Std All Material Responses Overall Or Ams 4967 Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Aluminum Alloy Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rievet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL111VAZ6-3](https://military-fasteners.com/pins/pin_rivets/HL111VAZ6-3) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.