

P/N HL111VAZ6-4

Military-Fasteners.com

#### Description

Flush shear head, oversized titanium

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	HL111VAZ64
Minimum Qty (MOQ):	10
NSN:	5320-01-414-9116
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



# P/N HL111VAZ6-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.565 Inches Minimum And 0.585 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.2016 Inches Minimum And 0.2026 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.2966 Inches Minimum And 0.3016 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.245 Inches Minimum And 0.255 Inches Maximum
Minimum Tensile Strength:	2000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	6130 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	1/64" Oversize
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Hi-shear Spec.294, Cage 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	73197-hl111 Manufacturers Standard

## How to Order

Order this pin-rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/pin\_rivets/HL111VAZ6-4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.