

Description

Flush shear head, oversized titanium

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL111VAZ66
Minimum Qty (MOQ):	25
NSN:	5320-01-373-4919
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N HL111VAZ6-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.690 Inches Minimum And 0.710 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.201 Inches Minimum And 0.206 Inches Maximum
Shank Style:	Pin-rievet, Tapered, Threaded
Head Major Diameter:	0.296 Inches Minimum And 0.301 Inches Maximum
Tip Diameter:	0.181 Inches Minimum And 0.184 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.370 Inches Minimum And 0.380 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	2000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	6130 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std All Material Responses Overall Or Ams 4967 Assn Std All Material Responses Overall
Surface Treatment:	Aluminum Alloy Overall
Thread Series Designator:	Unf

How to Order

Order this pin-rievet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL111VAZ6-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.