

Description

HL11V6-8 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[HL18PB6-11](#)

SKU / Model:	HL11V68
Minimum Qty (MOQ):	5
NSN:	5320-00-151-5460
Schedule B:	8108.90.8000
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N HL11V6-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.815 Inches Minimum And 0.835 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.079 Inches Minimum And 0.080 Inches Maximum
Shank Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.297 Inches Minimum And 0.302 Inches Maximum
End Item Identification:	W/s:aircraft, Prowler Ea-6b; Global Hawk High Altitude-long Endurance Unmanned Aerial Vehicle; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Aircraft, Tomcat F-14; Aircraft, Galaxy C-5; Aircraft, Thunderbolt II, A-10; Aircraft, F-111; Aircraft, Stratolifter C-135; Aircraft, Hornet F/a-18; Aircraft, Eagle F-15
Grip Length:	0.505 Inches Maximum
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL11V6-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.