

**Description**

flush shear head, titanium

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL11VAZ53
Minimum Qty (MOQ):	10
NSN:	5320-00-338-5682
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N HL11VAZ5-3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Width Between Flats:</b>	0.063 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.1625 Inches Minimum And 0.1635 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.256 Inches Minimum And 0.261 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.193 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Surface Treatment Document And Classification:</b>	294,fscm 73197 Mfr Ref Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL11VAZ5-3](https://military-fasteners.com/rivets/pin_rivets/HL11VAZ5-3) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.