

Description

Flush shear head, titanium

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL11VAZ56
Minimum Qty (MOQ):	10
NSN:	5320-00-185-0907
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N HL11VAZ5-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.677 Inches Minimum And 0.697 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0635 Inches Minimum And 0.0645 Inches Maximum
Shank Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.2564 Inches Minimum And 0.2612 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.380 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	294,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL11VAZ5-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.