

Description

100°, flush shear head - titanium

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL11VAZ58
Minimum Qty (MOQ):	2
NSN:	5320-01-494-8615
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N HL11VAZ5-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0635 Inches Minimum And 0.0645 Inches Maximum
Shank Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.2564 Inches Minimum And 0.2612 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.495 Inches Minimum And 0.505 Inches Maximum
Nominal Thread Size:	0.164 Inches
Countersink Angle:	100.0 Degrees Nominal
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std 1st Material Response Overall Or Ams 4967 Assn Std 2nd Material Response Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL11VAZ5-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.