

P/N HL11VAZ6-3

Military-Fasteners.com

## Description

flush shear head, titanium

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

Order this part online

## **Additional Information**

SKU / Model:	HL11VAZ63
Minimum Qty (MOQ):	10
NSN:	5320-00-178-8716
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



## P/N HL11VAZ6-3 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Fastener Length:	0.502 Inches Minimum And 0.522 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.2966 Inches Minimum And 0.3016 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.192 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	294,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

## How to Order

Order this pin-rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/pin\_rivets/HL11VAZ6-3</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.