

Description

HL11VAZ6-5 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL11VAZ65
Minimum Qty (MOQ):	10
NSN:	5320-01-617-1373
ECCN:	EAR99



* See page 2 for technical characteristics

P/N HL11VAZ6-5 Specifications

Thread Class:	M3a
Thread Direction:	Right-hand
Fastener Length:	0.947 Inches Minimum And 0.967 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.2966 Inches Minimum And 0.3016 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
End Item Identification:	C-5 Reliability Enhancement Re-engining Program
Grip Length:	0.562 Inches Nominal
Thread Quantity Per Inch:	B32
Minimum Tensile Strength:	2000 Pounds Per Square Inch
Nominal Thread Size:	0.188 Inches
Shear Strength:	5380 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Part Name Assigned By Controlling Agency:	Pin, Flush, Reduced
Special Features:	Color Black On Threads; 32 Microinch Finish
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Hi-shear Spec 294 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL11VAZ6-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.