

**Description**

Flush shear head, titanium

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL11VAZ67
Minimum Qty (MOQ):	5
NSN:	5320-01-499-5878
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

## P/N HL11VAZ6-7 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.753 Inches Minimum And 0.773 Inches Maximum
<b>Head Style:</b>	Cooper's
<b>Head Height:</b>	0.065 Inches Maximum
<b>Shank Diameter:</b>	0.1610 Inches Minimum And 0.1640 Inches Maximum
<b>Shank Style:</b>	Stump
<b>Head Major Diameter:</b>	0.301 Inches Maximum
<b>Expansion Device:</b>	Threaded Sleeve
<b>Grip Length:</b>	0.428 Inches Minimum And 0.438 Inches Maximum
<b>Nominal Thread Size:</b>	0.312 Inches
<b>Shear Strength:</b>	95000 Double Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Special Features:</b>	Threaded End Of Pin Is Chamfered 0.031 Inches At 45 Degrees
<b>Material:</b>	Titanium Alloy Uns R54520 Overall
<b>Material Document And Classification:</b>	Ams-4928 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this pin-rievet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rievets/HL11VAZ6-7](https://military-fasteners.com/pins/pin_rievets/HL11VAZ6-7) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.