

P/N HL11VAZ6-9

Description

HL11VAZ6-9 Pin-rivet, flush shear head - titanium

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: HL11VAZ69

Minimum Qty (MOQ): 10

NSN: 5320-01-499-5875

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed







^{*} See page 2 for technical characteristics

P/N HL11VAZ6-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.877 Inches Minimum And 0.897 Inches Maximum
Head Style:	Cooper's
Head Height:	0.065 Inches Maximum
Shank Diameter:	0.1610 Inches Minimum And 0.1640 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.301 Inches Maximum
Expansion Device:	Threaded Sleeve
Grip Length:	0.552 Inches Minimum And 0.562 Inches Maximum
Nominal Thread Size:	0.312 Inches
Shear Strength:	95000 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Threaded End Of Pin Is Chamferred 0.031 Inches At 45 Degrees
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Ams-4928 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL11VAZ6-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/pin_rivets/HL11VAZ6-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/pin_rivets/HL11VAZ6-9 and selecting the quantity you want then click "add to cart".