

Description

HL11VAZ6-9 Pin-rivet, flush shear head - titanium

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL11VAZ69
Minimum Qty (MOQ):	10
NSN:	5320-01-499-5875
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N HL11VAZ6-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.877 Inches Minimum And 0.897 Inches Maximum
Head Style:	Cooper's
Head Height:	0.065 Inches Maximum
Shank Diameter:	0.1610 Inches Minimum And 0.1640 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.301 Inches Maximum
Expansion Device:	Threaded Sleeve
Grip Length:	0.552 Inches Minimum And 0.562 Inches Maximum
Nominal Thread Size:	0.312 Inches
Shear Strength:	95000 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Threaded End Of Pin Is Chamfered 0.031 Inches At 45 Degrees
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Ams-4928 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL11VAZ6-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.