

Description

HL11VF5-4 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[HL11VF-5-4](#)

SKU / Model:	HL11VF54
Minimum Qty (MOQ):	20
NSN:	5320-01-375-9791
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N HL11VF5-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0635 Inches Minimum And 0.0645 Inches Maximum
Shank Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-riquet, Straight, Threaded
Head Major Diameter:	0.2564 Inches Minimum And 0.2612 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.245 Inches Minimum And 0.255 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	1200 Pounds Per Square Inch
Nominal Thread Size:	0.164 Inches
Shear Strength:	4010 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Surface Coating Hi-shear Spec 305 Ty 1,color Blue
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Asm 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	73197-hl11vf-5-4 Manufacturers Standard

How to Order

Order this pin-riquet from our inventory online by visiting https://military-fasteners.com/pins/pin_riquets/HL11VF5-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.