

Description

Fastener Length: 61/64", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | HL11VF610 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-341-5685 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |



NO IMAGE
AVAILABLE

P/N HL11VF6-10 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Identification Code Color: | Blue |
| Fastener Length: | 0.945 Inches Minimum And 0.955 Inches Maximum |
| Head Style: | Flush Countersunk |
| Width Between Flats: | 0.0791 Inches Minimum And 0.0806 Inches Maximum |
| Shank Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.2966 Inches Minimum And 0.3016 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Grip Length: | 0.620 Inches Minimum And 0.630 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 95000 Pounds Per Square Inch |
| Nominal Thread Size: | 0.190 Inches |
| Shear Strength: | 5380 Double Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Titanium Alloy Uns R54520 Overall |
| Material Document And Classification: | Ams4967 Mfr Ref Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 73197-hl11vf-6-10 Manufacturers Standard |

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL11VF6-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.