

Description

Fastener Length: 41/64", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL11VF65
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-317-6770
Schedule B:	8108.90.3060
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N HL11VF6-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Identification Code Color:	Blue
Fastener Length:	0.627 Inches Minimum And 0.647 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.2966 Inches Minimum And 0.3016 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.307 Inches Minimum And 0.317 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	95000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	5380 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Ams4967 Mfr Ref Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	73197-hl11vf-6-5 Manufacturers Standard

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL11VF6-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.