

P/N HL11VF6-6

Military-Fasteners.com

#### Description

Fastener Length: 45/64", Thread Size: 13/64', Hi-Lok, HL11 series pin

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	HL11VF66
Minimum Qty (MOQ):	10
NSN:	5320-01-313-1401
Schedule B:	8108.90.3060
ECCN:	EAR99



# P/N HL11VF6-6 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Identification Code Color:	Blue
Fastener Length:	0.690 Inches Minimum And 0.710 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.2966 Inches Minimum And 0.3016 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.370 Inches Minimum And 0.380 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	95000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	5380 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Ams4967 Mfr Ref Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	73197-hl11vf-6-6 Manufacturers Standard

## How to Order

Order this pin-rivet from our inventory online by visiting <u>https://military-fasteners.com/pins/pin\_rivets/HL11VF6-6</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.