

## **P/N HL11VF6-9**

## **Description**

Fastener Length: 45/64", Thread Size: 3/16", HL11 series pin

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: HL11VF69

Minimum Qty (MOQ):

NSN: 5320-01-342-3724

Schedule B: 8108.90.3060

ECCN: EAR99









# **P/N HL11VF6-9 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Identification Code Color:	Blue
Fastener Length:	0.690 Inches Minimum And 0.710 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.2966 Inches Minimum And 0.3016 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.558 Inches Minimum And 0.568 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	95000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	5380 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Ams4967 Mfr Ref Single Material Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this pin-rivet from our inventory online by visiting <a href="https://military-fasteners.com/pins/pin\_rivets/HL11VF6-9">https://military-fasteners.com/pins/pin\_rivets/HL11VF6-9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.