

Description

Thread Size: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL128710
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-407-5416
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HL1287-10 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.552 Inches Minimum And 0.558 Inches Maximum
Collar Overall Height:	0.700 Inches Maximum
Lubrication:	Cetyl Alcohol
Collar Inside Diameter:	0.367 Inches Minimum And 0.373 Inches Maximum
Nominal Thread Size:	0.3125 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	For 0.0468 Oversized Rivets.
Material:	Steel Comp 303 Overall
Material Document And Classification:	Mil-s-764 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	81205-bacc30u Manufacturers Standard

How to Order

Order this collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL1287-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.