

**Description**

Thread Size: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL128710
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-407-5416
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N HL1287-10 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.552 Inches Minimum And 0.558 Inches Maximum
<b>Collar Overall Height:</b>	0.700 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Collar Inside Diameter:</b>	0.367 Inches Minimum And 0.373 Inches Maximum
<b>Nominal Thread Size:</b>	0.3125 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Special Features:</b>	For 0.0468 Oversized Rivets.
<b>Material:</b>	Steel Comp 303 Overall
<b>Material Document And Classification:</b>	Mil-s-764 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	81205-bacc30u Manufacturers Standard

## How to Order

Order this collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HL1287-10](https://military-fasteners.com/collars/pin_rivet+collars/HL1287-10) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.