

Description

HL12VAZ8-11 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL12VAZ811
Minimum Qty (MOQ):	5
NSN:	5320-01-499-5881
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

P/N HL12VAZ8-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.073 Inches Minimum And 1.093 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.2410 Inches Minimum And 0.2440 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.415 Inches Minimum And 0.440 Inches Maximum
Grip Length:	0.678 Inches Minimum And 0.688 Inches Maximum
Nominal Thread Size:	0.250 Inches
Shear Strength:	95000 Double Pounds Per Square Inch
Special Features:	Threaded End Of Pin Is Chamfered 0.031 Inches At 37 Degrees
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Ams-4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rievet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL12VAZ8-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.