

Description

Pin-rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[HL12VF6-11](#)

SKU / Model:

HL12VF611

Minimum Qty (MOQ):

10

NSN:

5320-01-372-7193

ECCN:

EAR99

NO IMAGE
AVAILABLE

P/N HL12VF-6-11 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 1.003 Inches Minimum And 1.023 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.064 Inches Minimum And 0.074 Inches Maximum |
| Width Between Flats: | 0.0791 Inches Minimum And 0.0806 Inches Maximum |
| Shank Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Shank Style: | Pin-riquet, Straight, Threaded |
| Head Major Diameter: | 0.357 Inches Minimum And 0.377 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Grip Length: | 0.683 Inches Minimum And 0.693 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 3180 Pounds Per Square Inch |
| Nominal Thread Size: | 0.190 Inches |
| Shear Strength: | 5380 Double Pounds Per Square Inch |
| Special Features: | Surface Coating Hi-shear Spec 305,ty 1,color Blue |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 73197-hl12vf-6-11 Manufacturers Standard |

How to Order

Order this pin-riquet from our inventory online by visiting https://military-fasteners.com/pins/pin_riquets/HL12VF-6-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.