

**Description**

HL12VF5-5 Pin-Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL12VF55
Minimum Qty (MOQ):	10
NSN:	5320-01-342-3725
ECCN:	EAR99



NO IMAGE  
AVAILABLE

## P/N HL12VF5-5 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.614 Inches Minimum And 0.634 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.055 Inches Minimum And 0.060 Inches Maximum
<b>Width Between Flats:</b>	0.064 Inches Minimum And 0.065 Inches Maximum
<b>Shank Diameter:</b>	0.163 Inches Minimum And 0.164 Inches Maximum
<b>Shank Style:</b>	Pin-riquet, Straight, Threaded
<b>Head Major Diameter:</b>	0.306 Inches Minimum And 0.322 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Grip Length:</b>	0.317 Inches Maximum
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-riquet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_riquets/HL12VF5-5](https://military-fasteners.com/pins/pin_riquets/HL12VF5-5) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.