

Description

Fastener Length: 1-63/64", Thread Size: 1/4", HL18 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL18PB1024
Minimum Qty (MOQ):	5
NSN:	5320-00-354-8561
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N HL18PB10-24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Identification Code Color:	Bronze
Fastener Length:	1.990 Inches Minimum And 2.010 Inches Maximum
Head Style:	Err-090
Head Height:	0.068 Inches Minimum And 0.078 Inches Maximum
Width Between Flats:	0.1270 Inches Minimum And 0.1295 Inches Maximum
Shank Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Shank Style:	Pin-riivet, Straight, Threaded
Head Major Diameter:	0.475 Inches Minimum And 0.500 Inches Maximum
Grip Length:	1.495 Inches Minimum And 1.505 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.312 Inches
Shear Strength:	96000 Single Pounds Per Square Inch
Heat Treatment:	As Fabricated Overall
Material:	Steel Overall
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-riivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL18PB10-24 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.