

Description

protruding shear head, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | HL18PB108 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-145-1947 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |

NO IMAGE
AVAILABLE

P/N HL18PB10-8 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Identification Code Color: | Bronze |
| Fastener Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Head Height: | 0.068 Inches Minimum And 0.078 Inches Maximum |
| Width Between Flats: | 0.127 Inches Minimum And 0.130 Inches Maximum |
| Shank Diameter: | 0.311 Inches Minimum And 0.312 Inches Maximum |
| Shank Style: | Pin-riquet, Straight, Threaded |
| Head Major Diameter: | 0.475 Inches Minimum And 0.505 Inches Maximum |
| Grip Length: | 0.505 Inches Maximum |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Nominal Thread Size: | 0.312 Inches |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Material: | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-riquet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL18PB10-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.