

Description

Diameter: 5/32", Grip Length: 3/4", protruding shear head, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL18PB512 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5320-00-959-7201 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N HL18PB5-12 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Identification Code Color: | Bronze |
| Fastener Length: | 1.052 Inches Minimum And 1.072 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.037 Inches Minimum And 0.047 Inches Maximum |
| Width Between Flats: | 0.079 Inches Minimum And 0.080 Inches Maximum |
| Shank Diameter: | 0.163 Inches Minimum And 0.164 Inches Maximum |
| Shank Style: | Pin-riquet, Straight, Threaded |
| Head Major Diameter: | 0.242 Inches Minimum And 0.262 Inches Maximum |
| Grip Length: | 0.755 Inches Maximum |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Nominal Thread Size: | 0.164 Inches |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Material: | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this pin-riquet from our inventory online by visiting https://military-fasteners.com/pins/pin_riquets/HL18PB5-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.