

## **P/N HL18PB6-3**

### **Description**

Diameter: 3/16", Grip Length: 3/16", protruding shear head, alloy steel cadmium plated

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: HL18PB63

Minimum Qty (MOQ): 20

NSN: 5320-00-959-7214

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9









<sup>\*</sup> See page 2 for technical characteristics

# **P/N HL18PB6-3 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.503 Inches Minimum And 0.523 Inches Maximum
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.080 Inches Maximum
Shank Diameter:	0.189 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
End Item Identification:	Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p);engine, Aircraft, J-57 All Models (c-135, Ec-135, B-52);aircraft, Sof (Ac-130h, Mc-130h, Ec-130e,hc-130);helicopter, Search And Rescue, Hh-60h;engine, Aircraft Tf33-p-3/5/9 (c/ec-135, B-52h);aircraft, C-2a (reprocured);helicopter, Mh-53e;engine, Aircraft, Tf-33-p-7 (c-141a/b);helicopter, Carrier Based Asw, Sh-60f.
Grip Length:	0.193 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this pin-rivet from our inventory online by visiting <a href="https://military-fasteners.com/pins/pin">https://military-fasteners.com/pins/pin</a> rivets/HL18PB6-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/pins/pin">https://military-fasteners.com/pins/pin</a> rivets/HL18PB6-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/pins/pin">https://military-fasteners.com/pins/pin</a> rivets/HL18PB6-3 and selecting the quantity you want then click "add to cart".