P/N HL18PB6-34

Description

Fastener Length: 2-1/2",

* Manufacturer certifications are shipped with your order ~~FREE~~ of charge

Order this part online

Additional Information

SKU / Model:	HL18PB634
Minimum Qty (MOQ):	1
NSN:	5320-01-477-2607
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

* See page 2 for technical characteristics

P/N HL18PB6-34 Specifications

Fastener Length:	2.480 Inches Minimum And 2.520 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Shank Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin Rivet, Threaded
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Grip Length:	2.120 Inches Minimum And 2.130 Inches Maximum
Part Name Assigned By Controlling Agency:	Protruding Shear Head Alloy Steel1/16 In. Grip Variation
Special Features:	Thread 10-32unjf-3a Modified; Socket Hex. 0.0791 Min 0.0808 Max, Depth 0.115 Min 0.135 Max, Dia. 0.104 Min 0.119 Max; Double Shear Pounds Min. 5,380; Tension Pounds Min. 2,500; Head Chamfer 1/32 In. X 45 Deg
Material:	Steel Overall
Material Document And Classification:	Mil-s-5000 Mil Std 1st Material Response Overall Or Mil-s-5626 Mil Std 2nd Material Response Overall Or Mil-s-6049 Mil Std 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Type Ii Class 2 Color Bronze And Cetyl Alcohol Lube Per Hi-shear Spec 305 Fed Spec Single Treatment Response Overall

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL18PB6-34 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.