

Description

Fastener Length: 2-1/2",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | HL18PB634 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5320-01-477-2607 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N HL18PB6-34 Specifications

| | |
|---|---|
| Fastener Length: | 2.480 Inches Minimum And 2.520 Inches Maximum |
| Head Style: | Straight Pan |
| Head Height: | 0.045 Inches Minimum And 0.055 Inches Maximum |
| Shank Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Shank Style: | Pin Rivet, Threaded |
| Head Major Diameter: | 0.295 Inches Minimum And 0.315 Inches Maximum |
| Grip Length: | 2.120 Inches Minimum And 2.130 Inches Maximum |
| Part Name Assigned By Controlling Agency: | Protruding Shear Head Alloy Steel1/16 In. Grip Variation |
| Special Features: | Thread 10-32unjf-3a Modified; Socket Hex. 0.0791 Min 0.0808 Max, Depth 0.115 Min 0.135 Max, Dia. 0.104 Min 0.119 Max; Double Shear Pounds Min. 5,380; Tension Pounds Min. 2,500; Head Chamfer 1/32 In. X 45 Deg |
| Material: | Steel Overall |
| Material Document And Classification: | Mil-s-5000 Mil Std 1st Material Response Overall Or Mil-s-5626 Mil Std 2nd Material Response Overall Or Mil-s-6049 Mil Std 3rd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Type Ii Class 2 Color Bronze And Cetyl Alcohol Lube Per Hi-shear Spec 305 Fed Spec Single Treatment Response Overall |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL18PB6-34 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.