

**Description**

Diameter: 5/32", Grip Length: 1/2", flush shear head, alloy steel cadmium plated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL19PB58
Minimum Qty (MOQ):	20
NSN:	5320-00-959-0194
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N HL19PB5-8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.802 Inches Minimum And 0.822 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Width Between Flats:</b>	0.0791 Inches Minimum And 0.0801 Inches Maximum
<b>Shank Diameter:</b>	0.1625 Inches Minimum And 0.1635 Inches Maximum
<b>Shank Style:</b>	Pin-riquet, Straight, Threaded
<b>Head Major Diameter:</b>	0.2564 Inches Minimum And 0.2612 Inches Maximum
<b>Grip Length:</b>	0.495 Inches Minimum And 0.505 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-riquet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL19PB5-8](https://military-fasteners.com/pins/pin_rivets/HL19PB5-8) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.