

Description

flush shear head, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL19PB613
Minimum Qty (MOQ):	10
NSN:	5320-00-959-7303
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N HL19PB6-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.127 Inches Minimum And 1.147 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.2966 Inches Minimum And 0.3016 Inches Maximum
End Item Identification:	W/s: Aircraft, Starlifter C-141; Aircraft, Hx Unique; Helicopter, Hx Unique; Fms-a7 Aircraft; Joint Stars Target Radar System; Aircraft, F-111; Aircraft, Galaxy C-5; Aircraft, Stratolifter C-135; Aircraft, C-2a (reprocured); Engine, Aircraft, T56-a-7/15 (c-130b/e/h/n/p)
Grip Length:	0.807 Inches Minimum And 0.817 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL19PB6-13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.