

P/N HL19PB6-2

Description

Diameter: 3/16", Grip Length: 1/8", flush shear head, alloy steel cadmium plated, HL19 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

HL19PB-6-2

SKU / Model: HL19PB62

Minimum Qty (MOQ): 20

NSN: 5320-00-959-7307

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









P/N HL19PB6-2 Specifications

Thread Class:	
Thread Direction:	Right-hand
Fastener Length: 0.4	0.440 Inches Minimum And 0.460 Inches Maximum
Head Style: Flo	lush Countersunk
Nidth Between Flats: 0.0	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter: 0.	0.189 Inches Minimum And 0.190 Inches Maximum
Shank Style: Pir	in-rivet, Straight, Threaded
Head Major Diameter: 0.3	0.297 Inches Minimum And 0.302 Inches Maximum
Grip Length: 0.	0.130 Inches Maximum
Thread Quantity Per Inch: 32	22
Minimum Tensile Strength: 16	.60000 Pounds Per Square Inch
Nominal Thread Size: 0.	0.190 Inches
Shear Strength: 95	5000 Single Pounds Per Square Inch
Countersink Angle: 10	.00.0 Degrees Nominal
Material: St	steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Ail-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec Brd Material Response Overall
Surface Treatment: Ca	Cadmium Overall
Surface Treatment Document And Quassification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL19PB6-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.