

P/N HL19PB6-5

Description

Diameter: 3/16", Grip Length: 5/16", flush shear head, alloy steel cadmium plated, HL19 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: HL19PB65

Minimum Qty (MOQ): 20

NSN: 5320-00-969-4521

Schedule B: 7318.29.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









^{*} See page 2 for technical characteristics

P/N HL19PB6-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.627 Inches Minimum And 0.647 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.189 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.297 Inches Minimum And 0.302 Inches Maximum
Grip Length:	0.317 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL19PB6-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.