

Description

Pin-Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[HL20PB-10-16](#)

SKU / Model:	HL20PB1016
Minimum Qty (MOQ):	5
NSN:	5320-01-124-6660
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N HL20PB10-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.490 Inches Minimum And 1.510 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.098 Inches Minimum And 0.112 Inches Maximum
Width Between Flats:	0.1270 Inches Minimum And 0.1295 Inches Maximum
Shank Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Shank Style:	Pin-riquet, Straight, Threaded
Head Major Diameter:	0.472 Inches Minimum And 0.502 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.995 Inches Minimum And 1.005 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.312 Inches
Material:	Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-5626 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-riquet from our inventory online by visiting https://military-fasteners.com/pins/pin_riquets/HL20PB10-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.