

Description

Fastener Length: 3/4", Thread Size: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL20PB104
Minimum Qty (MOQ):	5
NSN:	5320-00-869-4297
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

P/N HL20PB10-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Err-090
Head Height:	0.098 Inches Minimum And 0.112 Inches Maximum
Width Between Flats:	0.127 Inches Minimum And 0.130 Inches Maximum
Shank Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
Shank Style:	Pin-riquet, Straight, Threaded
Head Major Diameter:	0.472 Inches Minimum And 0.502 Inches Maximum
Grip Length:	0.255 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.312 Inches
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-riquet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL20PB10-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.