

Description

Diameter: 5/32", Grip Length: 7/16", protruding tension head, alloy steel cadmium plated, HL20 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[HL20PB-5-7](#)

SKU / Model:	HL20PB57
Minimum Qty (MOQ):	20
NSN:	5320-00-814-1184
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N HL20PB5-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Err-090
Head Height:	0.055 Inches Minimum And 0.060 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.080 Inches Maximum
Shank Diameter:	0.163 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Grip Length:	0.443 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.164 Inches
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL20PB5-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.