

## Description

Diameter: 5/32", Grip Length: 7/16", protruding tension head, alloy steel cadmium plated, HL20 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[HL20PB-5-7](#)

SKU / Model:	HL20PB57
Minimum Qty (MOQ):	10
NSN:	5320-00-814-1184
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HL20PB5-7 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.740 Inches Minimum And 0.760 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.055 Inches Minimum And 0.060 Inches Maximum
<b>Width Between Flats:</b>	0.079 Inches Minimum And 0.080 Inches Maximum
<b>Shank Diameter:</b>	0.163 Inches Minimum And 0.164 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.306 Inches Minimum And 0.322 Inches Maximum
<b>Grip Length:</b>	0.443 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL20PB5-7](https://military-fasteners.com/pins/pin_rivets/HL20PB5-7) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.