

**Description**

Diameter: 3/16", Grip Length: 13/16", protruding tension head, alloy steel cadmium plated, HL20 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL20PB613
Minimum Qty (MOQ):	10
NSN:	5320-01-068-5545
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N HL20PB6-13 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	1.127 Inches Minimum And 1.147 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.064 Inches Minimum And 0.074 Inches Maximum
<b>Width Between Flats:</b>	0.0791 Inches Minimum And 0.0806 Inches Maximum
<b>Shank Diameter:</b>	0.1885 Inches Minimum And 0.1895 Inches Maximum
<b>Head Major Diameter:</b>	0.357 Inches Minimum And 0.377 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>End Item Identification:</b>	Ws: Helicopter,ch-53a/d/e; Aircraft,stratolifter C-135; Helicopter,green Giant H-3; Helicopter,sof/hh-53h Pave Low; Helicopter,kiowa Oh-58 A&c; Helicopter,electronic Countermeasures,eh-60a; Helicopter,sea King H-3; Helicopter,mh-53e; Helicopter,black Haw Uh-60a
<b>Grip Length:</b>	0.817 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Collar Style:</b>	Straight Type
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp H11 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-5000 Mil Spec 4th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rievet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL20PB6-13](https://military-fasteners.com/pins/pin_rivets/HL20PB6-13) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.