

Description

protruding tension head alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL20PB83 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5320-00-103-0725 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N HL20PB8-3 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.573 Inches Minimum And 0.593 Inches Maximum |
| Head Style: | Straight Pan |
| Head Height: | 0.077 Inches Minimum And 0.090 Inches Maximum |
| Width Between Flats: | 0.095 Inches Minimum And 0.097 Inches Maximum |
| Shank Diameter: | 0.249 Inches Minimum And 0.250 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.415 Inches Minimum And 0.440 Inches Maximum |
| End Item Identification: | Wsd: Helicopter, Mh-53e; Helicopter, Carrier Based Asw, Sh-60f; Helicopter, Sof/hh-53h Pave Low; Helicopter, Advance Attack, Ah-1w; Aircraft, Sof (ac-130h, Mc-130h, Ec-130e, Hc-130); Helicopter, Uscg Search And Rescue, Hh-60j; Joint Stars Target Radar System; Helicopter, Search And Rescue, Hh-60h; Aircraft, C-2a (reprocured) |
| Grip Length: | 0.193 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Criticality Code Justification: | Feat |
| Special Features: | Weapon System Essential |
| Material: | Steel Comp 4340 Or Steel Comp 8735 Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL20PB8-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.