

Description

protruding tension head alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL20PB83
Minimum Qty (MOQ):	20
NSN:	5320-00-103-0725
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL20PB8-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.573 Inches Minimum And 0.593 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.077 Inches Minimum And 0.090 Inches Maximum
Width Between Flats:	0.095 Inches Minimum And 0.097 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.250 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.415 Inches Minimum And 0.440 Inches Maximum
End Item Identification:	Wsd: Helicopter, Mh-53e; Helicopter, Carrier Based Asw, Sh-60f; Helicopter, Sof/hh-53h Pave Low; Helicopter, Advance Attack, Ah-1w; Aircraft, Sof (ac-130h, Mc-130h, Ec-130e, Hc-130); Helicopter, Uscg Search And Rescue, Hh-60j; Joint Stars Target Radar System; Helicopter, Search And Rescue, Hh-60h; Aircraft, C-2a (reprocured)
Grip Length:	0.193 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Criticality Code Justification:	Feat
Special Features:	Weapon System Essential
Material:	Steel Comp 4340 Or Steel Comp 8735 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL20PB8-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.