

Description

Fastener Length: 2-29/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL20PB834
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-567-7060
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N HL20PB8-34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	2.448 Inches Minimum And 2.468 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.077 Inches Minimum And 0.090 Inches Maximum
Width Between Flats:	0.122 Inches Minimum And 0.142 Inches Maximum
Shank Diameter:	0.248 Inches Minimum And 0.250 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.415 Inches Minimum And 0.440 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
End Item Identification:	A-10 Aircraft
Grip Length:	2.058 Inches Minimum And 2.068 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.250 Inches
Shear Strength:	9300 Double Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Pin-rivet
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams-s-6049 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams-p-416,type li.class 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL20PB8-34 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.