

**Description**

Fastener Length: 2-29/64", Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL20PB834
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-567-7060
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

## P/N HL20PB8-34 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	2.448 Inches Minimum And 2.468 Inches Maximum
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.077 Inches Minimum And 0.090 Inches Maximum
<b>Width Between Flats:</b>	0.122 Inches Minimum And 0.142 Inches Maximum
<b>Shank Diameter:</b>	0.248 Inches Minimum And 0.250 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.415 Inches Minimum And 0.440 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>End Item Identification:</b>	A-10 Aircraft
<b>Grip Length:</b>	2.058 Inches Minimum And 2.068 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Shear Strength:</b>	9300 Double Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Pin-rivet
<b>Material:</b>	Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Ams-s-6049 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams-p-416,type li.class 2 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL20PB8-34](https://military-fasteners.com/rivets/pin_rivets/HL20PB8-34) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.