

## P/N HL218-10-13

## **Description**

Fastener Length: 1-5/16", Thread Size: 1/4

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: HL2181013

Minimum Qty (MOQ): 10

NSN: 5320-01-218-0725

Schedule B: 7318.24.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N HL218-10-13 Specifications

| Thread Class:                                  | 3a  |
|--|---|
| Thread Direction:                              | Right-hand  |
| Identification Code Color:                     | Bronze  |
| Fastener Length:                               | 1.302 Inches Minimum And 1.322 Inches Maximum   |
| Head Style:                                    | Err-090   |
| Head Height:                                   | 0.068 Inches Minimum And 0.078 Inches Maximum   |
| Width Between Flats:                           | 0.1270 Inches Minimum And 0.1295 Inches Maximum   |
| Shank Diameter:                                | 0.3422 Inches Minimum And 0.3432 Inches Maximum   |
| Shank Style:                                   | Pin-rivet, Straight, Threaded   |
| Head Major Diameter:                           | 0.475 Inches Minimum And 0.505 Inches Maximum   |
| Lubrication:                                   | Cetyl Alcohol, Spec 305, Hi-shear Corp  |
| Grip Length:                                   | 0.807 Inches Minimum And 0.817 Inches Maximum   |
| Thread Quantity Per Inch:                      | 24  |
| Nominal Thread Size:                           | 0.312 Inches  |
| Material:                                      | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall  |
| Material Document And Classification:          | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall |
| Surface Treatment:                             | Cadmium Overall And Chromate Overall  |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall   |
| Thread Series Designator:                      | Unjf  |

### **How to Order**

Order this pin-rivet from our inventory online by visiting <a href="https://military-fasteners.com/pins/pin\_rivets/HL218-10-13">https://military-fasteners.com/pins/pin\_rivets/HL218-10-13</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/pins/pin\_rivets/HL218-10-13">https://military-fasteners.com/pins/pin\_rivets/HL218-10-13</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/pins/pin\_rivets/HL218-10-13">https://military-fasteners.com/pins/pin\_rivets/HL218-10-13</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/pins/pin\_rivets/HL218-10-13">https://military-fasteners.com/pins/pin\_rivets/HL218-10-13</a> and selecting the quantity you want then click "add to cart".